



ردیف قلم	شماره قطعه	مشخصات کالا	واحد	مقدار	بهاء واحد به عدد ((ریال))	بهاء واحد به حروف ((ریال))	قیمت کالا ((ریال))
		3ply Plastic Tape Inner wrap coating Cold applied 3-ply plastics extruded Tape as an external anti-corrosion - Coating by hand or hand machine to be used as inner- layer tape in tape. Coating systems to the exterior of Buried steel pipes,field weld joints and repair of PE coating pipe. It shall consist of stabilized polyethylene backing and butyl rubber adhesive layers on both sides Fully amalgamating within overlap area the butyl compound shall be firmly anchored to the polyethylene by the use of a co extruded layer from a blend of butyl rubber and polyethylene. The coating requirements shall be in accordance with the attachment table. The coating performance, test method and inspection shall be all in accordance with EN 12068, Packaging labeling shall be in accordance with IPS-M-TP-310 Application Temperature -10 to 50° C Service Temperature +25° C	RO	400			
1		3ply plastic tape inner wrap coating tape width 6 (in) , tape length 100(ft) NST 1000	RO	400			
2		Outer wrap plastic tape coating tape width 6 (in) , tape length 100(ft) NST 760	RO	200			
3		3ply plastic tape inner wrap coating tape width 4 (in) , tape length 100(ft) NST 1000	RO	200			
4		Outer wrap plastic tape coating tape width 4 (in) , tape length 100(ft) NST 760	RO	200			
5		Primer Application temperature: -10 to + 50°c Service temperature: +25 °c	LT	400			



ردیف قلم	شماره قطعه	مشخصات کالا	واحد	مقدار	بهاء واحد به عدد ((ریال))	بهاء واحد به حروف ((ریال))	قیمت کالا ((ریال))
		SNS_9930031					
		جهت تعمیرات اساسی خطوط لوله سال 1400 PRIMER FOR USING WITH COLD APPLIED INNER LAYER PLASTIC TAPE IN TAPE COATING SYSTEMS , IN , P 27 ACCORDANCE WITH IPS-M-TP-321  IN MOST ECONOMICAL PACK	LT	200			
		SNS_9930033					
		جهت تعمیرات اساسی خطوط لوله سال 1400 OUTER WRAP PLASTIC TAPE COATING COLD APPLIED LAMINATED PLASTIC TAPE TO BE USED AS OUTER - LAYER TYPE ( OUTER-WRAP) IN TAPE COATING SYSTEMS TO THE EXTERIOR OF BURIED STEEL PIPES THROUGH MECHANICAL METHOD IN ACCORDANCE WITH ,IPS-M-TP-311  WIDTH 4 IN., LENGTH 100 FT.	RO	100			
		WIDTH 6 IN., LENGTH 100 FT.	RO	100			



					INNER WRAP COLD APPLIED THREE - PLY PLASTICS EXTRUDED TAPE AS AN EXTERNAL ANTI -CORROSION COATING BY HAND OR HAND MACHINE. TO BE USED AS INNER-LAYER TAP IN TAPE COATING SYSTEMS TO THE EXTERIOR OF BURIED STEEL PIPES , FIELD WELD JOINTS AND REPAIR OF PE COATING PIPE. IT SHALL CONSIST OF STABILIZED POLYETHYLENE BACKING AND BUTYL RUBBER ADHESIVE LAYERS ON BOTH SIDES FULLY AMALGAMATING WITHIN OVERLAP ARCA. THE BUTYL COMPOUND SHALL BE FIRMLY ANCHORED TO POLYETHYLENE BY THE USE OF A CO EXTRUDED LAYER FROM A BLEND OF BUTYL RUBBER AND POLYETHYLENE THREE LAYERS INNER WRAP		
			100	RO	WIDTH 4 IN., LENGTH 100 FT.		3
			100	RO	WIDTH 6 IN., LENGTH 100 FT.		4
SAS_9940005							



					<p>LAMINATED POLYETHYLENE TAPE, "CO-EXTRUDE OUTER WRAP,  "COMPOSITION: STABILIZED POLYETHYLENE  " BACKING AND LAMINATED POLYETHYLENE  "TAPE, CO-EXTRUDE OUTER WRAP,  "COMPOSITION: STABILIZED POLYETHYLENE  "BACKING AND BUTYL RUBBER SYNTHETIC  "ELASTOMER-ADHESIVE RESIN, ELANGATION 400%  ", DIELECTRIC STRENGTH 40 KV/MM, APPLICATION  "TEMPERATURE RANGE: -20 TO 60 DEG. C. NST 750,  ", TOTAL THK. 750 MIC.,  "TENSILE STRENGTH 9.0 KG/CM,  WIDTH 6 IN., LENGTH 100 FT. نوار پوشش خارجی. ارائه گواهینامه فنی محصول و همچنین تاییدیه بازرسی فنی زاگرس جنوبی الزامی می باشد</p>		
			161	RO			1



					LAMINATED POLYETHYLENE TAPE, "INNER WRAP THE MAIN MATERIAL " USED ARE A STABILIZED POLYETHYLENE " BACKING LAMINATED POLYETHYLENE " TAPE, INNER WRAP THE MAIN MATERIAL USED ARE A STABILIZED "POLYETHYLENE BACKING AND BUTYL " RUBBER BASE SYNTHETIC ELASTOMER " ADHESIVE TOTAL THK. 1000 MIC. BACKING " THK. 450 MIC.ADHESIVE "TENSILE STRENGTH 8 KG/CM, "ELANGATION 400%  "WIDTH 6 IN., LENGTH 100 FT. نوار پوشش داخلی ارائه گواهینامه فنی محصول و همچنین تاییدیه بازرسی فنی زاگرس جنوبی الزامی می باشد"				
			154	RO				SAS_9940007	2



					<p>"ALTENE" PRIMER P 27</p> <p>"ADHESIONS PROMOTING RESINS &amp; RUBBERS</p> <p>" , BASE HEPTANES + TOLUENE, BLACK</p> <p>"USE FOR LAMINATED WRAPPING</p> <p>" TAPED REF. ALTENE, ITALY</p> <p>P-27 پرایمر ارائه گواهینامه فنی محصول تاییدیه بازرسی فنی زاگرس جنوبی الزامی می باشد.</p>			1
			154	LT				توضیحات
		به عدد	قیمت کل کالا					
		به حروف	((ریال))					
		به عدد	هزینه بسته بندی					
		به حروف	((ریال))					
		به عدد	هزینه حمل					
		به حروف	((ریال))					
		به عدد	جمع کل					
		به حروف	((ریال))					
		نام و امضاء و مهر فروشنده:			<p>شیراز خیابان زند جنب کوچه پروانه - ساختمان شرکت ملی نفت ایران - شرکت بهره برداری نفت و گاز زاگرس جنوبی (تدارکات کالا) - واحد 506 - روح الله پسنجدیده تلفن (07132138436) فاکس (07132314447) ایمیل ()</p>			