



ردیف قلم	شماره قطعه	مشخصات کالا	واحد	مقدار	بهاء واحد به عدد ((ریال))	بهاء واحد به حروف ((ریال))	قیمت کالا ((ریال))
1		<p>Description for Corrosion Inhibitor of Film Forming Type, Oil Soluble and Water Dispersible for Continuous Injection in down hole and Flow Line Application in Gas Field:</p> <ul style="list-style-type: none"> <li>-Designed for Prevention of Corrosion in Gas Field (Production, Gathering, Separation and Transportation Systems) include Gas, Gas Condensate and Water.</li> <li>-Effective against Corrosive Attacking in System Containing: Carbon Dioxide (Co2:~1.8% mole), Hydrogen Sulfide (H2S: ~ 600ppm), Organic Acids and Corrosive Brines.</li> <li>-Contained Emulsion Prevention Chemical and shouldn't be Induce Emulsification in Gas Treatments Plants and Outstanding for use in Continuous Treating Applications.</li> <li>- Exhibited good Filming Characteristics in Continuous Treating Application.</li> <li>- Should be High Thermal Stability (Up to 100°C)</li> <li>- Filed test result in south zagros oil &amp; Gas Production Company is necessary.</li> </ul> <p>انجام بازرسی حین تولید و آزمونهای کنترل کیفیت مطابق با دستورالعمل اداره حفاظت فنی شرکت زاگرس جنوبی شامل نمونه برداری و انجام بررسی های آزمایشگاهی ضروری است.</p>	LT	64064			
SSS_0030031							



			31824	LT	<p>Description for Corrosion Inhibitor of Film Forming Type, Oil Soluble and Water Dispersible for Continuous Injection in down hole and Flow Line                  Application in Gas Field:                  -Designed for Prevention of Corrosion in Gas Field (Production, Gathering, Separation and Transportation Systems) include Gas, Gas Condensate and Water.                  -Effective against Corrosive Attacking in System Containing: Carbon Dioxide (Co2:~1.8% mole), Hydrogen Sulfide (H2S: ~ 600ppm), Organic Acids and Corrosive Brines.                  -Contained Emulsion Prevention Chemical and shouldn't be Induce Emulsification in Gas Treatments Plants and Outstanding for use in Continuous Treating Applications.                  - Exhibited good Filming Characteristics in Continuous Treating Application.                  - Should be High Thermal Stability (Up to 100°C)                  - Filed test result in south zagros oil &amp; Gas Production Company is necessary.                  انجام بازرسی حین تولید و آزمونهای کنترل کیفیت مطابق با دستورالعمل اداره حفاظت فنی شرکت زاگرس جنوبی شامل نمونه برداری و انجام بررسی های آزمایشگاهی ضروری است.</p>			مواد ضد خوردگی پیوسته	1
								SNS_0030013	



			55000	LT	<p>ماده بازدارنده خوردگی تزریق پیوسته سرچاهی و درون چاهی</p> <p>Description for Corrosion Inhibitor of Film Forming Type, Oil Soluble and Water Dispersible for Continuous Injection in down hole and Flow Line Application in Gas Field:</p> <p>-Designed for Prevention of Corrosion in Gas Field (Production, Gathering, Separation and Transportation Systems) include Gas, Gas Condensate and Water.</p> <p>-Effective against Corrosive Attacking in System Containing: Carbon Dioxide (Co2:~1.8% mole), Hydrogen Sulfide (H2S: ~ 600ppm), Organic Acids and Corrosive Brines.</p> <p>-Contained Emulsion Prevention Chemical and shouldn't be Induce Emulsification in Gas Treatments Plants and Outstanding for use in Continuous Treating Applications.</p> <p>- Exhibited good Filming Characteristics in Continuous Treating Application.</p> <p>- Should be High Thermal Stability (Up to 100°C)</p> <p>- Filed test result in south zagros oil &amp; Gas Production Company is necessary.</p> <p>انجام بازرسی حین تولید و آزمونهای کنترل کیفیت مطابق با دستورالعمل اداره حفاظت فنی شرکت زاگرس جنوبی شامل نمونه برداری و انجام بررسی های آزمایشگاهی ضروری است.</p>		1
ZRS_0031049							



			58864	LT	<p>Description for Corrosion Inhibitor of Film Forming Type, Oil Soluble and Water Dispersible for Continuous Injection in down hole and Flow Line Application in Gas Field:</p> <ul style="list-style-type: none"> <li>-Designed for Prevention of Corrosion in Gas Field (Production, Gathering, Separation and Transportation Systems) include Gas, Gas Condensate and Water.</li> <li>-Effective against Corrosive Attacking in System Containing: Carbon Dioxide (Co<sub>2</sub>:~1.8% mole), Hydrogen Sulfide (H<sub>2</sub>S: ~ 600ppm), Organic Acids and Corrosive Brines.</li> <li>-Contained Emulsion Prevention Chemical and shouldn't be Induce Emulsification in Gas Treatments Plants and Outstanding for use in Continuous Treating Applications.</li> <li>- Exhibited good Filming Characteristics in Continuous Treating Application.</li> <li>- Should be High Thermal Stability (Up to 100°C)</li> <li>- Filed test result in south zagros oil &amp; Gas Production Company is necessary.</li> </ul> <p>انجام بازرسی حین تولید و آزمونهای کنترل کیفیت مطابق با دستورالعمل اداره حفاظت فنی شرکت زاگرس جنوبی شامل نمونه برداری و انجام بررسی های آزمایشگاهی ضروری است.</p> <p>ماده بازدارنده خوردگی تزریق پیوسته سر چاهی</p>		1
					توضیحات		
		به عدد	قیمت کل کالا				
		به حروف	((ریال))				
		به عدد	هزینه بسته بندی				
		به حروف	((ریال))				
		به عدد	هزینه حمل				
		به حروف	((ریال))				
		به عدد	جمع کل				
		به حروف	((ریال))				
نام و امضاء و مهر فروشنده:				شیراز خیابان زند جنب کوچه پروانه - ساختمان شرکت ملی نفت ایران - شرکت بهره برداری نفت و گاز زاگرس جنوبی (تدارکات کالا) - واحد 506 - روح الله پسندیده تلفن (07132138436) فاکس (07132314447) ایمیل ()			