



| ردیف قلم | شماره قطعه | مشخصات کالا                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | واحد | مقدار | بهاء واحد به عدد ((ریال)) | بهاء واحد به حروف ((ریال)) | قیمت کالا ((ریال)) |
|----------|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-------|---------------------------|----------------------------|--------------------|
| 1        |            | COPPER WIRE, BARE, STRANDED, HARD DRAWN,<br>IN ACC. WITH ISIRI-109 OR IEC-28 OR BS-125<br>NOTE FOR O/H LINES AND EARTHING<br>REF: IKO-IRAN, IRAN-BAYKA OR APPROVED EQUIV.<br>NOM. CROSS NO./DIA.<br>SECT. AREA OF STRANDS<br><br>25 SQ MM 7/2.13 MM<br>سیم ارت مسی 7 رشته 25 میل                                                                                                                                                                                                                                             | MT   | 200   |                           |                            |                    |
| 2        |            | 70 SQ. MM. 7/3.55 MM.<br>سیم ارت مسی 7 رشته 70 میل                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | MT   | 100   |                           |                            |                    |
| 3        |            | FLEXIBLE CORD, VR BRAIDED, 250/440 VOLTS - CONDUCTORS OF<br>TINNED COPPER WIRES, INSULATED<br><br>NOM. CROSS NO./DIA.<br>SECT. AREA OF STRANDS<br><br>0.75 SQ.MM 24/.20 MM 3 core<br>کابل افشان 0.75*3 میلیمتر                                                                                                                                                                                                                                                                                                               | MT   | 100   |                           |                            |                    |
| 4        |            | FLEX.C.250/440V.2CORE CON.H.C.P.A.C.W,FLEX.STRA. - PVC<br>INS.COR.LAID PARAL.W/BS6004/VDE283/DIN47716 -<br><br>NOM. CROSS NO./DIA.<br>SECT. AREA OF STRANDS<br><br>0.50 SQ.MM 16/.20 MM<br>کابل افشان 0.5*2 میلیمتر                                                                                                                                                                                                                                                                                                          | MT   | 300   |                           |                            |                    |
| 5        |            | FLEX.C.300/500V,CIRC.COND.H.C.P.A.C.WIRES,FL.ST. -<br>PVC.INS.PVC.SHEA.O.,M.W/ISIRI607&VDE250&DIN47718 - FLEXIBLE<br>CORD, 300/500 VOLTS, CIRCULAR, - CONDUCTORS OF HIGH<br>CONDUCTIVITY PLAIN - ANNEALED COPPER WIRES, FLEXIBLY<br>STRANDED, - PVC INSULATED, PVC SHEATHED OVERALL, - MAT<br>IN ACC. WITH ISIRI 607 OR VDE 0250 - OR DIN 47718 - NOTE TO BE<br>ORDERED IN REELS OF 100 METERS - REF: IKO-IRAN OR<br>APPROVED EQUIVALENT - KHM-035 - KHM-454<br><br>1.0 SQ.MM TWIN CORE 32/.20 MM.<br>کابل افشان 1*2 میلیمتر | MT   | 300   |                           |                            |                    |
| 6        |            | 1.5 SQ.MM TWIN CORE 30/.25 MM.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | MT   | 400   |                           |                            |                    |



| ردیف قلم | شماره قطعه | مشخصات کالا                                                                                                                                                                                                                                                                                                                                                                                                                     | واحد | مقدار | بهاء واحد به عدد ((ریال)) | بهاء واحد به حروف ((ریال)) | قیمت کالا ((ریال)) |
|----------|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-------|---------------------------|----------------------------|--------------------|
|          |            | کابل افشان 2*1.5 میلیمتر                                                                                                                                                                                                                                                                                                                                                                                                        |      |       |                           |                            |                    |
| 7        |            | FLEXIBLE CORD, VR BRAIDED, 250/440 VOLTS - CONDUCTORS OF TINNED COPPER WIRES, INSULATED - FLEXIBLE CORD, VR BRAIDED, 250/440 VOLTS, - CONDUCTORS OF TINNED COPPER WIRES, INSULATED - WITH VULCANISED RUBBER, CORES TWISTED - TOGETHER, COTTON FILLED AND BRAIDED, 3 CORE, - COLOURED MAROON OR WITH OTHER COMBINATION OF - COLOURS. - FOR DOMESTIC APPLIANCES<br><br>2.5 SQ.MM TWIN CORE 50/.25 MM.<br>کابل افشان 2*2.5 میلیمتر | MT   | 200   |                           |                            |                    |
| 8        |            | 2.5 SQ.MM THREE CORE 50/.25 MM.<br>کابل افشان 3*2.5 میلیمتر                                                                                                                                                                                                                                                                                                                                                                     | MT   | 350   |                           |                            |                    |
| 9        |            | CABLE FOR CONDUIT WIRING, 450/750 V. GRADE, - CONDUCTORS - OF HIGH CONDUCTIVITY PLAIN - ANNEALED COPPER, PVC INSULATED, SINGLE CORE - MAT: IN ACC. WITH BS 6004 OR VDE OR - DIN 47702 - REF IRAN BAYKA, IKO IRAN OR APPROVED 0250 EQUIV. - KHM-035 - KHM-454<br><br>.BLUE 6.0 SQ.MM. 84/.30 MM<br>سیم افشان آبی                                                                                                                 | MT   | 1000  |                           |                            |                    |
| 10       |            | CABLE F/CONDUIT W.,450/750V.GRADE COND.H.C.P.A.C - PVC INS.SINGLE CORE,MAT.W/BS6004/VED250/DIN47702<br><br>YELLOW 6.0 SQ.MM. 84/.30 MM.<br>سیم افشان زرد                                                                                                                                                                                                                                                                        | MT   | 300   |                           |                            |                    |
| 11       |            | CABLE FOR CONDUIT WIRING, 450/750 V. GRADE, - CONDUCTORS - OF HIGH CONDUCTIVITY PLAIN - ANNEALED COPPER, PVC INSULATED, SINGLE CORE - MAT: IN ACC. WITH BS 6004 OR VDE OR - DIN 47702 - REF IRAN BAYKA, IKO IRAN OR APPROVED 0250 EQUIV. - KHM-035 - KHM-454<br><br>.RED 6.0 SQ.MM. 84/.30 MM<br>سیم افشان قرمز                                                                                                                 | MT   | 300   |                           |                            |                    |
| 12       |            | BLACK 6.0 SQ.MM. 84/.30 MM.<br>سیم افشان مشکی                                                                                                                                                                                                                                                                                                                                                                                   | MT   | 1000  |                           |                            |                    |
| 13       |            | 4.0 SQ.MM FOUR CORE<br>کابل افشان 4*4                                                                                                                                                                                                                                                                                                                                                                                           | MT   | 400   |                           |                            |                    |
| 14       |            | 16 SQ.MM FOUR CORE 128/.40 MM. -<br>کابل افشان 4*16                                                                                                                                                                                                                                                                                                                                                                             | MT   | 350   |                           |                            |                    |



| ردیف قلم | شماره قطعه | مشخصات کالا                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | واحد | مقدار | بهاء واحد به عدد ((ریال)) | بهاء واحد به حروف ((ریال)) | قیمت کالا ((ریال)) |
|----------|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-------|---------------------------|----------------------------|--------------------|
| 15       |            | WELDING CABLE, 200 VOLT GRADE<br>CONDUCTORS OF HIGH CONDUCTIVITY TINNED<br>ANNEALED SUPERFLEXIBLY STRANDED COPPER WIRES<br>LAID UP IN FORM OF ROPE, INSULATED WITH<br>VULCANISED RUBBER,SHEATHED WITH OIL<br>RESISTANT POLYCHLOROPRENE, SINGLE CORE,<br>MATERIAL IN ACC. WITH BS 638 TABLE 1 OR<br>VDE 0250, STRANDING IN ACC. WITH BS 6007<br>NOM. CROSS NO./DIA.<br>SECT. AREA OF STRANDS<br><br>50 SQ.MM 1018/.25 MM 200/.40 MM.<br>کابل جوشکاری 50                                                                                | MT   | 100   |                           |                            |                    |
| 16       |            | UNDERGROUND CABLE, 0.6/1 KV,<br>CONDUCTORS OF HIGH CONDUCT. PLAIN ANNEALED<br>COPPER WIRES, PVC INSULATED, PVC FILLED AND<br>EXTRUDED, LEAD SHEATHED, PVC BEDDED,ARMOURED<br>WITH A SINGLE LAYER OF GALVANIZED STEEL<br>WIRES, BLACK PVC SERVED OVERALL<br>MAT: IN ACC. WITH VDE 0265 OR BS 6346<br>NOTE WHEN ORDERING SPECIFY THE INDIVIDUAL<br>LENGTHS REQUIRED<br>NOM. CROSS NO. & DIA. CORES<br>SECT. AREA OF STRANDS SHAPE<br><br>3X 6+2X2.5 FIVE ROUND<br>کابل ارموردار زیرزمینی                                                | MT   | 400   |                           |                            |                    |
| 17       |            | 3X10+2X2.5 FIVE ROUND<br>کابل ارموردار زیرزمینی                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | MT   | 700   |                           |                            |                    |
| 18       |            | 3X16+2X2.5 FIVE ROUND<br>کابل ارموردار زیرزمینی                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | MT   | 300   |                           |                            |                    |
| 19       |            | U.G.C, 600/1000 V.,C.H.C.W.PVC INS. PVC BED. ARMO. -<br>GALV.S.W.PVC RESI.MOIS.&OIL&CHE.W/VDE0271&BS6346 - U.G.<br>CABLE, 600/1000 V., CONDUCTORS OF HICH - CONDUCT. PLAIN<br>ANNEALED COPPER WIRES, - PVC INSULATED, PVC FILLED AND<br>EXTRUDED, - PVC BEDDED, ARMOURED WITH A SINGLE LAYER<br>OF - GALVANIZED STEEL WIRES, BLACK PVC SERVED - OVERALL,<br>PVC RESISTANT AGAINST - MOISTURE, OILS & CHEMICALS - MAT:<br>IN ACC. WITH VDE-0271 OR BS-6346 - NOTE WHEN ORDERING<br>SPECIFY THE INDIVIDUAL - LENGTHS REQUIRED - KHM-454 | MT   | 100   |                           |                            |                    |



| ردیف قلم | شماره قطعه | مشخصات کالا                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | واحد | مقدار | بهاء واحد به عدد ((ریال)) | بهاء واحد به حروف ((ریال)) | قیمت کالا ((ریال)) |
|----------|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-------|---------------------------|----------------------------|--------------------|
|          |            | 2.5 SQ.MM. THREE CORE<br>کابل زمینی 2.5*3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |      |       |                           |                            |                    |
| 20       |            | 10 SO.MM THREE CORE<br>کابل زمینی 1*3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | MT   | 200   |                           |                            |                    |
| 21       |            | 16 SQ.MM THREE CORE<br>کابل زمینی 16*3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | MT   | 200   |                           |                            |                    |
| 22       |            | 2.5 FOUR ROUND<br>کابل زمینی 2.5*4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | MT   | 200   |                           |                            |                    |
| 23       |            | 4.0 FOUR ROUND<br>کابل زمینی 4*4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | MT   | 100   |                           |                            |                    |
| 24       |            | 6.0 FOUR ROUND<br>کابل زمینی 6*4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | MT   | 100   |                           |                            |                    |
| 25       |            | 10 FOUR ROUND<br>کابل زمینی 10*4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | MT   | 100   |                           |                            |                    |
| 26       |            | 16 FOUR ROUND<br>کابل زمینی 16*4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | MT   | 100   |                           |                            |                    |
| 27       |            | 3X 25+ 16 FOUR ROUND<br>کابل زمینی ارموردار                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | MT   | 200   |                           |                            |                    |
| 28       |            | 3X 35+ 16 FOUR ROUND                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | MT   | 100   |                           |                            |                    |
| 29       |            | 3X 50+ 25 FOUR SHAPED                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | MT   | 400   |                           |                            |                    |
| 30       |            | 3X 70+ 35 FOUR SHAPED                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | MT   | 350   |                           |                            |                    |
| 31       |            | 3X120+ 70 FOUR SHAPED                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | MT   | 300   |                           |                            |                    |
| 32       |            | 3X150+ 70 FOUR SHAPED                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | MT   | 300   |                           |                            |                    |
| 33       |            | U.G.C.,6/1KV.C.H.C.P.A.C.W,PVC INS.PVC RESI.OIL -<br>&MOIS.&FLAME&CHEM.PVC FIL&EXTR.B.PVC.S.O.-BS6346 -<br>UNDERGROUND CABLE, 600/1000 VOLTS, - CONDUCTORS OF HIGH<br>CONDUCTIVITY, PLAIN - ANNEALED COPPER WIRES, PVC<br>INSULATED, PVC - FILLED & EXTRUDED, BLACK PVC SERVED<br>OVERALL, - MAT: IN ACC. WITH VDE 0271 OR BS 6346, - PVC<br>MATERIAL TO BE RESISTANT AGAIST FLAME, - MOISTURE, OIL &<br>CHEMICAL, ALSO SUITABLE - FOR SERVICE TEMP. OF MIN. 60 DEG.<br>C. - NOTE WHEN ORDERING SPECIFY THE INDIVIDUAL - LENGTHS<br>REQUIRED - KHM-454 - NOM. CROSS NO./DIA. CROSS -<br>SECT. AREA OF STRANDS SHAPE<br>16 SQ.MM SINGLE CORE 7/1.70 MM ROUND | MT   | 1800  |                           |                            |                    |



| ردیف قلم | شماره قطعه | مشخصات کالا                                                         | واحد | مقدار | بهاء واحد به عدد ((ریال)) | بهاء واحد به حروف ((ریال)) | قیمت کالا ((ریال)) |
|----------|------------|---------------------------------------------------------------------|------|-------|---------------------------|----------------------------|--------------------|
|          |            | کابل زمینی بدون ارمور 16*1                                          |      |       |                           |                            |                    |
| 34       |            | 25 SQ.MM SINGLE CORE 7/2.13 MM ROUND<br>کابل زمینی بدون ارمور 25*1  | MT   | 100   |                           |                            |                    |
| 35       |            | 35 SQ.MM SINGLE CORE 19/1.53 MM ROUND<br>کابل زمینی بدون ارمور 35*1 | MT   | 300   |                           |                            |                    |
| 36       |            | 50 SQ.MM SINGLE CORE 19/1.83 MM ROUND<br>کابل زمینی بدون ارمور 50*1 | MT   | 500   |                           |                            |                    |
|          |            | ZRS_0331544                                                         |      |       |                           |                            |                    |
| 1        |            | کابل مسی افشان 3*1.5 بدون آرمر                                      | MT   | 300   |                           |                            |                    |
| 2        |            | کابل مسی افشان 3*2.5 بدون آرمر                                      | MT   | 500   |                           |                            |                    |
| 3        |            | کابل مسی افشان 3*4 بدون آرمر                                        | MT   | 300   |                           |                            |                    |
| 4        |            | کابل مسی افشان 4*6 بدون آرمر                                        | MT   | 300   |                           |                            |                    |
| 5        |            | کابل مسی افشان 5*6 بدون آرمر                                        | MT   | 300   |                           |                            |                    |
| 6        |            | سیم مسی سبیل 1.5 رنگ آبی (30 رشته - قطر 0.25)                       | MT   | 2000  |                           |                            |                    |
| 7        |            | سیم مسی سبیل 1.5 رنگ قرمز (30 رشته - قطر 0.25)                      | MT   | 2000  |                           |                            |                    |
| 8        |            | سیم مسی سبیل 1.5 رنگ زرد-سبز (ارت) (30 رشته - قطر 0.25)             | MT   | 500   |                           |                            |                    |
| 9        |            | سیم مسی سبیل 2.5 رنگ آبی (50 رشته - قطر 0.25)                       | MT   | 2000  |                           |                            |                    |
| 10       |            | سیم مسی سبیل 2.5 رنگ قرمز (50 رشته - قطر 0.25)                      | MT   | 2000  |                           |                            |                    |
| 11       |            | سیم مسی سبیل 2.5 رنگ زرد-سبز (ارت) (30 رشته - قطر 0.25)             | MT   | 2000  |                           |                            |                    |
| 12       |            | سیم مسی سبیل 4 رنگ آبی (50 رشته - قطر 0.3)                          | MT   | 1500  |                           |                            |                    |
| 13       |            | سیم مسی سبیل 4 رنگ قرمز (50 رشته - قطر 0.3)                         | MT   | 2000  |                           |                            |                    |
| 14       |            | سیم مسی سبیل 4 رنگ سبز-زرد (ارت) (50 رشته - قطر 0.3)                | MT   | 2000  |                           |                            |                    |
| 15       |            | سیم مسی سبیل 6 رنگ آبی (84 رشته - قطر 0.3)                          | MT   | 2000  |                           |                            |                    |
| 16       |            | سیم مسی سبیل 6 رنگ قرمز (84 رشته - قطر 0.3)                         | MT   | 2000  |                           |                            |                    |
| 17       |            | سیم مسی سبیل 6 رنگ سبز-زرد (ارت) (84 رشته - قطر 0.3)                | MT   | 2000  |                           |                            |                    |
| 18       |            | کابل مسی تک رشته نیمه افشان روکش مشکی سبیل 16                       | MT   | 500   |                           |                            |                    |
| 19       |            | کابل مسی تک رشته نیمه افشان روکش مشکی سبیل 25                       | MT   | 300   |                           |                            |                    |
| 20       |            | کابل مسی تک رشته نیمه افشان روکش مشکی سبیل 35                       | MT   | 300   |                           |                            |                    |



|  |  |  |      |    |                                                                                                                                                                                                                                     |  |    |
|--|--|--|------|----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
|  |  |  | 200  | MT | سیم مسی افشان ارت (کلاس 5) سایز 10 (سبز-زرد)                                                                                                                                                                                        |  | 21 |
|  |  |  | 300  | MT | سیم مسی نیمه افشان ارت (کلاس 2) سایز 10 (سبز-زرد)                                                                                                                                                                                   |  | 22 |
|  |  |  | 1500 | MT | سیم افشان شماره 1/5 سیاه (رول 100 متری)                                                                                                                                                                                             |  | 23 |
|  |  |  | 1500 | MT | سیم افشان شماره 2/5 رنگ سیاه                                                                                                                                                                                                        |  | 24 |
|  |  |  | 1500 | MT | سیم افشان شماره 4 رنگ سیاه                                                                                                                                                                                                          |  | 25 |
|  |  |  | 1500 | MT | سیم افشان شماره 6 رنگ سیاه                                                                                                                                                                                                          |  | 26 |
|  |  |  | 1000 | MT | کابل آنتن برقی (رول 100 متری)                                                                                                                                                                                                       |  | 27 |
|  |  |  |      |    | SNS_0330036                                                                                                                                                                                                                         |  |    |
|  |  |  |      |    | اصلاحیه حذف اقلام 41 الی 51<br>تقاضای سالیانه 1403 اقلام مستمر<br>(گروه کالایی 68)<br>منطقه عملیاتی نار و کنگان                                                                                                                     |  |    |
|  |  |  |      |    | CABLES<br>COPPER WIRE,PVC,INSULATION,<br>690/1000 VOLTS SINGLE CORE WITH<br>FINE STRANDED COPPER CONDUCTOR<br>MAT. IN ACC. WITH IEC-60227-3,<br>NOTE FOR BUILDING WIRE<br>NOM. CROSS INSULATION WIRE<br>SEC. AREA THICKNESS DIA.    |  |    |
|  |  |  | 100  | MT | 2.5SQ.MM 0.8 MM 3.7 MM                                                                                                                                                                                                              |  | 1  |
|  |  |  | 100  | MT | 4 SQ.MM 0.8 MM 4.3 MM                                                                                                                                                                                                               |  | 2  |
|  |  |  |      |    | COPPER WIRE, BARE,<br>STRANDED, HARD DRAWN,<br>IN ACC. WITH ISIRI-109<br>IN ACC. WITH ISIRI-109<br>NOTE FOR O/H LINES AND EARTHING<br>REF IKO-IRAN,<br>IRAN-BAYKA OR APPROVED EQUIV.<br>NOM. CROSS NO./DIA<br>SECT. AREA OF STRANDS |  |    |
|  |  |  | 200  | MT | 25 SQ MM 7/2.13 MM                                                                                                                                                                                                                  |  | 3  |



|  |  |  |      |    |                                                                                                                                                                                                                                                                                                                                                                                                                  |  |    |
|--|--|--|------|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
|  |  |  | 800  | MT | FLEXIBLE CORD, VR BRAIDED,<br>250/440 VOLTS - CONDUCTORS OF TINNED COPPER WIRES,<br>INSULATED - FLEXIBLE CORD, VR BRAIDED, 250/440 VOLTS, -<br>CONDUCTORS OF TINNED COPPER WIRES, INSULATED - WITH<br>VULCANISED RUBBER, CORES TWISTED - TOGETHER, COTTON<br>FILLED AND BRAIDED, 3 CORE, - COLOURED MAROON OR WITH<br>OTHER COMBINATION OF - COLOURS. -<br>FOR DOMESTIC APPLIANCES<br><br>2.5 SQ.MM 50/.25 MM B9 |  | 4  |
|  |  |  | 100  | MT | FLEXIBLE CORD, 300/500 VOLTS,<br>CIRCULAR, CONDUCTORS OF HIGH<br>CONDUCTIVITY PLAIN ANNEALED<br>COPPER WIRES, FLEXIBLE<br>STRANDED, PVC INSULATED,<br>PVC SHEATHED OVERALL,<br>MAT IN ACC. WITH ISIRI 607<br>OR VDE 0250<br>NOM. CROSS NO. & DIA.<br>SEC. AREA OF STRANDS<br><br>1.5 SQ.MM TWIN CORE , 30/.25 MM                                                                                                 |  | 5  |
|  |  |  | 500  | MT | 2.5 SQ.MM, TWIN CORE , 50/.25 MM                                                                                                                                                                                                                                                                                                                                                                                 |  | 6  |
|  |  |  | 1000 | MT | 1.5 SQ.MM , THREE CORE , 30/.25 MM                                                                                                                                                                                                                                                                                                                                                                               |  | 7  |
|  |  |  | 1000 | MT | 2.5 SQ.MM , THREE CORE , 50/.25 MM                                                                                                                                                                                                                                                                                                                                                                               |  | 8  |
|  |  |  | 400  | MT | 4.0 SQ.MM , THREE CORE , 50/.30 MM                                                                                                                                                                                                                                                                                                                                                                               |  | 9  |
|  |  |  | 100  | MT | 10 SQ.MM , FOUR CORE                                                                                                                                                                                                                                                                                                                                                                                             |  | 10 |
|  |  |  | 100  | MT | 6.0 SQ.MM , FOUR CORE , 84/.30 MM                                                                                                                                                                                                                                                                                                                                                                                |  | 11 |
|  |  |  | 1500 | MT | CABLE FOR CONDUIT WIRING,<br>450/750V. GRADE, CONDUCTORS<br>OF HIGH CONDUCTIVITY PLAIN<br>ANNEALED COPPER,<br>PVC INSULATED, SINGLE CORE<br>MAT IN ACC. WITH BS 6004<br>OR VDE 0250 OR<br>COLOUR NOM. CROSS NO. & DIA.<br>SEC. AREA OF STRANDS<br><br>BLUE 2.5 SQ.MM , 50/.25 MM                                                                                                                                 |  | 12 |



|  |  |  |      |    |                             |  |    |
|--|--|--|------|----|-----------------------------|--|----|
|  |  |  | 1000 | MT | BLUE 4.0 SO.MM , 56/30 MM   |  | 13 |
|  |  |  | 200  | MT | BLUE 6.0 SO.MM , 84/30 MM   |  | 14 |
|  |  |  | 100  | MT | BLUE 10.0 SO.MM , 80/40 MM  |  | 15 |
|  |  |  | 200  | MT | BLUE 16.0 SQ.MM , 7/1.73 MM |  | 16 |
|  |  |  | 600  | MT | YELLOW 2.5 SQ.MM , 50/25 MM |  | 17 |
|  |  |  | 500  | MT | YELLOW 4.0 SQ.MM , 56/30 MM |  | 18 |
|  |  |  | 100  | MT | YELLOW 6.0 SQ.MM , 84/30 MM |  | 19 |
|  |  |  | 300  | MT | GREEN/YELLOW 1.5 SQ.MM      |  | 20 |
|  |  |  | 400  | MT | GREEN/YELLOW 2.5 SQ.MM      |  | 21 |
|  |  |  | 200  | MT | BROWN 1.5 SQ.MM , 30/25 MM  |  | 22 |
|  |  |  | 1000 | MT | BROWN 2.5 SQ.MM , 50/25 MM  |  | 23 |
|  |  |  | 450  | MT | BROWN 4.0 SQ.MM , 56/30 MM  |  | 24 |
|  |  |  | 200  | MT | BROWN 6.0 SQ.MM , 84/30 MM  |  | 25 |
|  |  |  | 200  | MT | WHITE 1.5 SQ.MM , 30/25 MM  |  | 26 |
|  |  |  | 1000 | MT | RED 2.5 SQ.MM , 50/25 MM    |  | 27 |
|  |  |  | 300  | MT | RED 4.0 SQ.MM , 56/30 MM    |  | 28 |
|  |  |  | 1000 | MT | BLACK 2.5 SQ.MM , 50/25 MM  |  | 29 |
|  |  |  | 300  | MT | BLACK 4.0 SQ.MM , 56/30 MM  |  | 30 |
|  |  |  | 400  | MT | GREEN 2.5 SQ.MM , 50/25 MM  |  | 31 |
|  |  |  | 300  | MT | GREEN 4.0 SQ.MM , 56/30 MM  |  | 32 |



|  |  |  |     |    |                                                                                                                                                                                                                                                                                                                                                  |  |    |
|--|--|--|-----|----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
|  |  |  | 200 | MT | FLEXIBLE CABLE,<br>450/750 VOLTS GRADE,<br>CONDUCTORS OF HIGH<br>CONDUCTIVITY TINNED<br>ANNEALED COPPER WIRES,<br>FLEXIBLY STRANDED,<br>RUBBER INSULATED,<br>RUBBER FILLED, OIL<br>RESISTANT, HEAVY TOUGH<br>RUBBER SERVED OVERALL<br>MAT IN ACC. WITH VDE 0250<br>AND DIN 47710 OR BS 6007<br>NOM. CROSS NO. & DIA.<br><br>4.0 SQ.MM THREE CORE |  | 33 |
|  |  |  | 200 | MT | 10.0 SQ.MM FOUR CORE 80/040MM                                                                                                                                                                                                                                                                                                                    |  | 34 |
|  |  |  | 500 | MT | FLEXIBLE CORD, 450/750 V.<br>GRADE, HEAVY DUTY,<br>CONDUCTORS OF HIGH<br>CONDUCTIVITY PLAIN<br>ANNEALED COPPER WIRES,<br>FLEXIBLY STRANDED,<br>PVC INSULATED,<br>PVC SHEATHED OVERALL<br>MAT IN ACC. WITH BS 6004<br>OR VDE 0250 OR DIN 47709/10<br>NOM. CROSS NO. & DIA.<br><br>2.5 SQ.MM TWIN CORE 50/.25MM                                    |  | 35 |
|  |  |  | 200 | MT | 6.0 SQ.MM THREE CORE 80/.30MM                                                                                                                                                                                                                                                                                                                    |  | 36 |
|  |  |  | 100 | MT | 1.5 SQ.MM FOUR CORE 30/.25MM                                                                                                                                                                                                                                                                                                                     |  | 37 |
|  |  |  | 100 | MT | 2.5 SQ.MM FOUR CORE 50/.25MM                                                                                                                                                                                                                                                                                                                     |  | 38 |
|  |  |  | 150 | MT | 10.0 SQ.MM FOUR CORE 80/.40MM                                                                                                                                                                                                                                                                                                                    |  | 39 |



|  |  |  |     |    |                                                                                                                                                                                                                                                                                                                                                                                                                                                       |    |
|--|--|--|-----|----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
|  |  |  | 200 | MT | U.G. CABLE, 0.6/1 KV,<br>CONDUCTORS OF HIGH CONDUCT.<br>PLAIN ANNEALED COPPER WIRES,<br>PVC INSULATED, PVC FILLED<br>AND EXTRUDED, PVC BEDDED,<br>ARMOURED WITH A SINGLE LAYER OF<br>GALVANIZED STEEL WIRES,<br>BLACK PVC SERVED OVERALL,<br>PVC RESISTANT AGAINST MOISTURE,<br>OILS & CHEMICALS<br>MAT IN ACC. WITH VDE-0271,<br>BS-6346 & IEC-60502<br>NOM. CROSS NO.&DIA.OF CORES<br>SECT. AREA STRANDS SHAPE<br><br>4.0 SO.MM THREE CORE 7/0.85MM | 40 |
|  |  |  | 0   | NO | CABLE LUG, STRAIGHT,<br>CRIMPING (CLOSED) TYPE,<br>HOT-TINNED COPPER,<br>WITH CYLINDRICAL OR OVAL SLEEVE<br>CONDUCTOR BOLT HOLE SLEEVE<br>C.S.A. DIA. MM. I.D. MM.<br><br>10 SQ.MM 8-10 4.5                                                                                                                                                                                                                                                           | 41 |
|  |  |  | 0   | NO | 16 SQ.MM 8-10 5.5                                                                                                                                                                                                                                                                                                                                                                                                                                     | 42 |
|  |  |  | 0   | NO | 25 SQ.MM 10-12 7                                                                                                                                                                                                                                                                                                                                                                                                                                      | 43 |
|  |  |  | 0   | NO | 35 SQ.MM 10-12 8.9                                                                                                                                                                                                                                                                                                                                                                                                                                    | 44 |
|  |  |  | 0   | NO | CABLE TIE, SELF LOCKING,<br>FELXIBLE PLASTIC OR NYLON 66,<br>NON RETURN.<br><br>LENGTH WIDE<br><br>450 MM. , 4.8 MM.                                                                                                                                                                                                                                                                                                                                  | 45 |



|  |  |  |     |    |                                                                                                                                                       |  |    |
|--|--|--|-----|----|-------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
|  |  |  |     |    | TAPE, PLASTIC, SELF ADHESIVE,<br>FOR HEAVY DUTY TAPING JOBS<br>AND EPOXY RESIN SPLICES OF<br>POWER CABLES,<br>THICKNESS 0.22 MM.                      |  |    |
|  |  |  | 0   | RO | 10-12 RED                                                                                                                                             |  | 46 |
|  |  |  | 0   | RO | 10-12 WHITE                                                                                                                                           |  | 47 |
|  |  |  | 0   | RO | 10-12 BLUE                                                                                                                                            |  | 48 |
|  |  |  | 0   | RO | 10-12 YELLOW                                                                                                                                          |  | 49 |
|  |  |  | 0   | RO | 10-12 GRREEN                                                                                                                                          |  | 50 |
|  |  |  | 0   | RO | 38-50 MM WIDE, BLACK                                                                                                                                  |  | 51 |
|  |  |  |     |    | ZVD_0300051                                                                                                                                           |  |    |
|  |  |  |     |    | اصلاحیه شماره 1 اصلاحیه افزایش قیمت<br>اقلام مورد نیاز واحذتعمیرات برق<br>منطقه عملیاتی سروستان و سعادت آباد-چاه های 7و8 سعادت آباد<br>کابل فشار ضعیف |  |    |
|  |  |  | 30  | MT | سیم برق افشان نرم مسی 1*16 میلیمتر مربع رنگ آبی                                                                                                       |  | 1  |
|  |  |  | 30  | MT | سیم برق افشان نرم مسی 1*16 میلیمتر مربع رنگ قرمز                                                                                                      |  | 2  |
|  |  |  |     |    | هادی مفتولی مسی 1 CLASS, 0.6/1kv, RM, N2XRY, PVC                                                                                                      |  |    |
|  |  |  | 360 | MT | کابل آرمردار 1*70 میلیمترمربع                                                                                                                         |  | 3  |
|  |  |  |     |    | هادی افشان نرم مسی 2 CLASS, 0.6/1kv, RM, NYRY, PVC                                                                                                    |  |    |
|  |  |  | 300 | MT | کابل آرمردار 4*4 میلیمترمربع                                                                                                                          |  | 4  |
|  |  |  | 60  | MT | کابل ارت مسی روکش دار سایز 35 میلیمتر مربع                                                                                                            |  | 5  |
|  |  |  | 120 | MT | کابل ارت مسی روکش دار سایز 70 میلیمتر مربع                                                                                                            |  | 6  |
|  |  |  | 190 | MT | کابل ارت مسی روکش دار سایز 50 میلیمتر مربع                                                                                                            |  | 7  |
|  |  |  | 100 | MT | کابل آرمردار 4*10 میلیمترمربع                                                                                                                         |  | 8  |
|  |  |  | 150 | MT | کابل آرمردار 4*6 میلیمترمربع                                                                                                                          |  | 9  |
|  |  |  | 180 | MT | کابل ارت مسی روکش دار سایز 16 میلیمتر مربع                                                                                                            |  | 10 |



|  |  |  |      |    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |  |    |
|--|--|--|------|----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
|  |  |  | 720  | MT | هادی مفتولی مسی 1 CLASS ,PVC , RM ,NYRY, 0.6/1kv<br>کابل آرمردار 1*35 میلیمتر مربع<br>باشد IEC60502-1 کلیه کابل ها باید مطابق استاندارد                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |  | 11 |
|  |  |  |      |    | SNS_0330056                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |    |
|  |  |  | 1000 | MT | جهت تعمیرات اساسی در سال 1404 منطقه عملیاتی ناروکنگان<br>INSTRUMENT CABLE 220V<br>INNER SHILDED GAL.<br>STEEL ARMORING<br>12 × 1.5 SQ.MM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |  | 1  |
|  |  |  | 500  | MT | کابل سامانه حفاظت کاتدیک اداره تعمیرات خطوط لوله<br>U.G CABLE 0.6/1 K V<br>CU/XLPE/PVC SINGLE CORE<br>استاندارد 750 IPS-M-TP-<br>SPECIFIC CABLE REQUIREMENTS<br>CABLE FOR USE AS A POSITIVE AND<br>NEGATIVE CONDUCTOR<br>SHALL BE SINGLE CORE<br>AND SOFT ANNEALED COPPER.<br>A DOUBLE JACKET OF CROSS-LINKED<br>POLYETHYLENE (XLPE) PRIMARY INSULATION<br>POLYVINYLCHLORIDE SHEATH.<br>THE AVERAGE THICKNESS OF CABLE<br>INSULATION SHALL BE 2.8 MM<br>FOR CONDUCTOR<br>SIZES UP TO 35 SQ.MM<br>AND 3 MM FOR LARGER SIZES. THE<br>MINIMUM THICKNESS<br>AT ANY POINT SHALL<br>NOT BE LESS THAN 90% OF THE<br>SPECIFIED AVERAGE THICKNESS<br>IN CASE OF DOUBLE JACKET THE<br>THICKNESS OF SHEATH SHALL<br>NOT BE LESS THAN 1.5 MM. |  | 2  |
|  |  |  | 1000 | MT | 1*25 SQ.MM SINGLE CORE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |  | 3  |
|  |  |  | 500  | MT | 1*35 SQ.MM SINGLE CORE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |  | 4  |
|  |  |  | 500  | MT | 1*50 SQ.MM SINGLE CORE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |  | 5  |



|                                                                                                                                                                                                                   |  |                             |                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------------------|-------------------|
|                                                                                                                                                                                                                   |  | توضیحات                     |                   |
|                                                                                                                                                                                                                   |  | قیمت کل کالا<br>((ریال))    | به عدد<br>به حروف |
|                                                                                                                                                                                                                   |  | هزینه بسته بندی<br>((ریال)) | به عدد<br>به حروف |
|                                                                                                                                                                                                                   |  | هزینه حمل<br>((ریال))       | به عدد<br>به حروف |
|                                                                                                                                                                                                                   |  | جمع کل<br>((ریال))          | به عدد<br>به حروف |
|                                                                                                                                                                                                                   |  | نام و امضاء و مهر فروشنده:  |                   |
| شیراز خیابان زند جنب کوچه پروانه - ساختمان شرکت ملی نفت ایران - شرکت بهره برداری نفت و گاز زاگرس جنوبی (تدارکات کالا) - واحد 502 - محسن محسنی نژاد تلفن (07132138336) فاکس ( ) ایمیل (m.mohseninezhad@szogpc.com) |  |                             |                   |