



ردیف قلم	شماره قطعه	مشخصات کالا	واحد	مقدار	بهاء واحد به عدد ((ریال))	بهاء واحد به حروف ((ریال))	قیمت کالا ((ریال))
		Globe Valve & Ball Valve for Parsian Gas Field مورد نیاز پروژه اصلاحیه فرآیندی ناحیه هما و شانول توضیحات: زمان تحویل اقلام تقاضا حداکثر شش ماه از زمان صدور سفارش خرید باشد محل تحویل اقلام در شهرستان لامرد، منطقه عملیاتی پارسیان اداره تدارکات کالای پارسیان Globe valve nominal size: 4" Pressure rating: class ANSI 1500 seat seal: metal to metal ends: flanged end RTJ design: straight type , bolted bonnet, outside screw & yoke END TO END: 546 mm disk type: plug equipped with lifting lugs and valve supports (legs) drain & vent connections are required body material: ASTM A216 WCB, bonnet material ASTM A216 WCB stem: ASTM A182 F6a CL2 seat ring: ASTM A105 + stellite Gr6 plug: ASTM A105 + 13cr overlay medium : sweet natural gas + condensate maximum design temprature: 100 centigrade degree minimum design temperature : -20 centigrade degree equipped with handwheel gearbox for operation gearbox dimension & design acc. To manufacturer standard fire test in acc to ISO 10497 (latest edition) design, dimension & test in acc to BS 1873 (1975) requiredsupplementary documentation: certificate of conformance to standard BS1873 pressure test report material inspection certificates in accordance with EN 10204 for metallic parts ; inspection certificate in acc to EN 10204 3.1 (2004) ; installation, operation and maintenance instructions/manuals general arrangements drawings cross-sectional drawings with parts and materials list; painting in acc to manufacturer recommendation	NO	1			
		Globe Valve & Ball Valve for Parsian Gas Field مورد نیاز پروژه اصلاحیه فرآیندی ناحیه هما و شانول	NO	1			



ردیف قلم	شماره قطعه	مشخصات کالا	واحد	مقدار	بهاء واحد به عدد ((ریال))	بهاء واحد به حروف ((ریال))	قیمت کالا ((ریال))
		Ball valve nominal size : 8" (full bore) Pressure rating : class ANSI 1500 ends: flanged end RTJ (R50) function : emergency shutdown valve Design : Three pieces body , Trunion mounted ball , Full Opening (full bore) , suitable for pigging operation , double block & bleed , Anti static device , equipped with sealant / lubricant injection fittings for seats & stem . body material: ASTM A105 Ball: A182 F6A CL.2 + ENP 0.003" SEAT RETAINER: ASTM A182 F6 BALL SEAT: NYLON , STEM: A182 F6 drain , vent & bypass connections is required equipped with lifting lugs and valve supports (legs) medium : sweet natural gas + condensate minimum design temperature : -20 centigrade degree end to end : 841 mm equipped with pneumatic spring return automatic actuator action : spring closing / air opening air working pressure of the actuator : 4 bar (g) actuator must be equipped with all required accessories for automatic actuating Design , dimension & test in acc to API 6D (2021- 25th Edition) ISO 14313(Edition 3) requiredsupplementary documentation: fire test in acc to ISO 10497 (latest edition) NDT in acc to API 6D annex A (A17 & A8 or A9) requiredsupplementary documentation in acc to API 6D annex C including : NDE records, certificate of conformance to Standard API 6D; pressure test report , fire test certificate; material inspection certificates in accordance with EN 10204 for metallic parts ; inspection certificate in acc to EN 10204 3.1 (2004) ; installation, operation and maintenance instructions/manuals general arrangements drawings cross-sectional drawings with parts and materials list; supplementary test requirements as per API 6D annex B (B5 & B10)					
3		GLOBE VALVE 4", FLGD, CLASS 900, RF	NO	4			



ردیف قلم	شماره قطعه	مشخصات کالا	واحد	مقدار	بهاء واحد به عدد ((ریال))	بهاء واحد به حروف ((ریال))	قیمت کالا ((ریال))
		GLOBE VALVE WITH THIS SPECIFICATION: STANDARD: BS1873 (1975) PRESSURE TEST ACC TO BS 6755 (PART1) (1986) SEAL: METAL SEAT-SECONDARY SOFT SEAL CERTIFICATION ACC TO BS-EN 10204/3.2 (2004) FLUID: SWEET GAS THE PAINTING PROTECTION OF THE VALVE SHALL BE IN ACCORDANCE WITH MANUFACTURERS OWN SPECIFICATION/PRACTICE DIFFERENTIAL PRESSURE ACROSS THE VALVE: 120 BAR BODY MATERIAL: A216 WCB BONNET MATT.: A216 WCB PLUG MATT.: A105/13cr OVERLAY STEM MATT.: 182-F6A CL.2 SEAT RING MATT.: A105/STELLITE , Gr6 1.6mm توضیحات: زمان تحویل اقلام تقاضا حداکثر شش ماه از زمان صدور سفارش خرید باشد محل تحویل اقلام در شهرستان لامرد، منطقه عملیاتی پارسپان اداره تدارکات کالای پارسپان					
توضیحات							
					به عدد	قیمت کل کالا	
					به حروف	((ریال))	
					به عدد	هزینه بسته بندی	
					به حروف	((ریال))	
					به عدد	هزینه حمل	
					به حروف	((ریال))	
					به عدد	جمع کل	
					به حروف	((ریال))	
نام و امضاء و مهر فروشنده:				شیراز خیابان زند جنب کوچه پروانه - ساختمان شرکت ملی نفت ایران - شرکت بهره برداری نفت و گاز زاگرس جنوبی (تدارکات کالا) - واحد 506 - سحر جره تلفن (32138442) فاکس (32314447) ایمیل ()			